# **Technical Data Sheet**



## Pigment Blue 15:6

#### **General Information**

Color Index	Pigment Blue 15:6 (C.I. 74160)		
Product Code	DuraPaint®6656		
CAS NO.	147-14-8		
EC No.	205-685-1		
Chemical Formula	C <sub>32</sub> H <sub>16</sub> CuN <sub>8</sub>		

### **Physical Properties**

Density (g/cm³)	1.55-1.65
Specific Surface Area(m²/g)	33-63
Oil Absorption (g/100g)	35-45
PH Value	6-8
Bulk Density (lb/gal)	12.4-14.1
Total impurities(ppm)	≤600

#### **Fastness Properties**

Heat Resistance (°C)	280	Alkali Resistance (1-5)
Light Resistance (Full Shade, 1-8)	7-8	Migration Resistance(1-5)
Light (Reduced tinting, 1-8)	7	Ethyl Acetate (1-5)
Weather Resistance (1-5)	5	Ethanol (1-5)
Acid Resistance (1-5)	5	MEK (1-5)

### **Application & Performance**

Recommended for Industrial paint, Coil coating, Powder coating, Decorative water/solvent-base paint, Automotive Refinish paint etc.

#### Note

Fineland Chem offers innovative pigment technologies designed for long-lastingperformance and consistent quality in industrial use. Product data is based oncurrent knowledge and for reference only. Users should verify suitability; no liability assumed for specific applications.

Date of issue: Sep. 1st, 2024

TDS Version: 2.1

5 5 5

China.

Tel: +86-571-83531793 Web: www.finelandchem.com