

# Technical Data Sheet

## Pigment Orange 34



FINELAND CHEM  
泛成化工

### General Information

Color Index	Pigment Orange 34 (C.I. 21115)
Product Code	DuraPaint®6234Y
CAS NO.	15793-73-4
EC No.	239-898-6
Chemical Formula	C <sub>34</sub> H <sub>28</sub> Cl <sub>2</sub> N <sub>8</sub> O <sub>2</sub>

### Physical Properties

Density (g/cm <sup>3</sup> )	1.35-1.45
Specific Surface Area(m <sup>2</sup> /g)	35
Oil Absorption (g/100g)	35-45
PH Value	6.0-9.0
Moisture Content (%)	≤2.0
Total impurities(ppm)	≤600

### Fastness Properties

Heat Resistance (°C)	200	Alkali Resistance (1-5)	4
Light Resistance (Full Shade, 1-8)	5-6	Migration Resistance(1-5)	3-4
Light (Reduced tinting, 1-8)	5	Ethyl Acetate (1-5)	4
Weather Resistance (1-5)	3-4	Ethanol (1-5)	4
Acid Resistance (1-5)	4	MEK (1-5)	3

### Application & Performance

Recommended for Industrial paint, Decorative water/solvent-base paint, Water based ink, Textile printing pigment, also used in Plastic. Its the yellowish shade.

### Note

Fineland Chem offers innovative pigment technologies designed for long-lasting performance and consistent quality in industrial use. Product data is based on current knowledge and for reference only. Users should verify suitability; no liability is assumed for specific applications.

Date of issue: Sep. 1<sup>st</sup>, 2024

TDS Version: 2.1

Hangzhou Fancheng Chemical Co., Ltd.  
Add: NO.776, JianSheYi Road, XiaoShan, HangZhou,  
ZheJiang, China.  
Tel: +86-571-83531793  
Web: www.finelandchem.com

Fineland Chem Co., Ltd.  
Add: Room 09 27/F, Ho King Commercial Centre, 2-16  
Fa Yuen Street, Mongkok, Kl, HK.