

Technical Data Sheet

Pigment Red 22



FINELAND CHEM
泛成化工

General Information

Color Index	Pigment Red 22 (C.I. 12315)
Product Code	DuraPrint®6522
CAS NO.	6448-95-9
EC No.	229-245-3
Chemical Formula	C ₂₄ H ₁₈ N ₄ O ₄

Physical Properties

Density (g/cm ³)	1.30-1.47
Specific Surface Area(m ² /g)	30
Oil Absorption (g/100g)	35-50
PH Value	6-9
Moisture Content (%)	≤2.5
Total impurities(ppm)	≤600

Fastness Properties

Heat Resistance (°C)	160	Alkali Resistance (1-5)	4
Light Resistance (Full Shade, 1-8)	4-5	Migration Resistance(1-5)	4
Light (Reduced tinting, 1-8)	4	Ethanol (1-5)	4
Weather Resistance (1-5)	3-4	Ethyl Acetate (1-5)	3
Acid Resistance (1-5)	4	MEK (1-5)	3

Application & Performance

Recommended for Water-based system with yellowish tone.

Note

Fineland Chem offers innovative pigment technologies designed for long-lasting performance and consistent quality in industrial use. Product data is based on current knowledge and for reference only. Users should verify suitability; no liability is assumed for specific applications.

Date of issue Sep 1st, 2024

TDS Version 2.1

Hangzhou Fancheng Chemical Co.,Ltd.
Add NO.776, JianSheYi Road, XiaoShan, HangZhou,
ZheJiang, China.
Tel +86-571-83531793
Web: www.finelandchem.com

Fineland Chem Co., Ltd.
Add Room 09 27/F, Ho King Commercial Centre, 2-16
Fa Yuen Street, Mongkok, K1, HK