# **Technical Data Sheet**



## **Pigment Yellow 12**

### **General Information**

Color Index	Pigment Yellow 12 (C.I. 21090)
Product Code	DuraPrint®S6152-OPQ
CAS NO.	6358-85-6
EC No.	228-787-8
Chemical Formula	C <sub>32</sub> H <sub>26</sub> Cl <sub>2</sub> N <sub>6</sub> O <sub>4</sub>

## **Physical Properties**

Density (g/cm³)	1.5-1.7
Specific Surface Area(m <sup>2</sup> /g)	21-63
Oil Absorption (g/100g)	30-35
PH Value	6-8
Moisture Content (%)	≤2.0
Total impurities(ppm)	≤600

#### **Fastness Properties**

Heat Resistance (°C)	160
Light Resistance (Full Shade, 1-8)	3
Light (Reduced tinting, 1-8)	2-3
Weather Resistance (1-5)	3
Acid Resistance (1-5)	4

Alkali Resistance (1-5)	4
Migration Resistance(1-5)	3
Ethanol (1-5)	4
Ethyl Acetate (1-5)	3
MEK (1-5)	2

### **Application & Performance**

Recommended for solvent-based ink, good opacity.

#### Note

Fineland Chem offers innovative pigment technologies designed for long-lastingperformance and consistent quality in industrial use. Product data is based oncurrent knowledge and for reference only. Users should verify suitability; no liability assumed for specific applications.

Date of issue: Sep. 1st, 2024

TDS Version: 2.1

Tel: +86-571-83531793 Web: www.finelandchem.com