Technical Data Sheet



Pigment Yellow 191

General Information

| Color Index | Pigment Yellow 191 (C.I. 18795) |
|------------------|---------------------------------|
| Product Code | DuraPlast®HGR-1 |
| CAS NO. | 129423-54-7 |
| EC No. | 403-530-4 |
| Chemical Formula | $C_{17}H_{13}CaCIN_4O_7S_2$ |

Physical Properties

| Density (g/cm³) | 1.7-1.8 |
|--|---------|
| Specific Surface Area(m ² /g) | 10-30 |
| Oil Absorption (g/100g) | 30-60 |
| PH Value | 5.0-7.5 |
| Bulk Density (lb/gal) | 3-5 |
| Total impurities(ppm) | ≤600 |

Fastness Properties

| Heat Resistance (°C) | 300 |
|------------------------------------|-----|
| Light Resistance (Full Shade, 1-8) | 7 |
| Light (Reduced tinting, 1-8) | 6 |
| Weather Resistance (1-5) | 4 |
| Acid Resistance (1-5) | 5 |

| | Alkali Resistance (1-5) | 5 |
|---------------------------|-------------------------|---|
| Migration Resistance(1-5) | | 5 |
| | Ethyl Acetate (1-5) | 4 |
| Ethanol (1-5) | | 4 |
| | MEK (1-5) | 4 |

Application & Performance

Recommended for Plastic (PO, PVC, EVA), Also use in PS,ABS.

Note

Fineland Chem offers innovative pigment technologies designed for long-lastingperformance and consistent quality in industrial use. Product data is based oncurrent knowledge and for reference only. Users should verify suitability; no liability assumed for specific applications.

Date of issue Sep. 1st, 2024

TDS Version 2.1