Technical Data Sheet



Solvent Yellow 98

General Information

Color Index	Solvent Yellow 98 (C.I. 56238)
Product Code	CorSol®3198
CAS NO.	12671-74-8
EC No.	232-318-2
Chemical Class	Thioxanthene
Hue	Bright Yellow

Physical Properties

Bulk Density (g/cm³)	0.35
, , , , ,	
Melting point ($^{\circ}\mathrm{C}$)	approx.115
Moisture(%)	≤0.5
Ash(%)	≤0.3
Insolubility(%)	≤0.3
PH Value	6-8
Fe Content(ppm)	≤1000

Fastness Properties

Heat Resistance ($^{\circ}$ C) in PS	300	Migration Resistance(1~5)	5
Light Resistance (Full Shade, 1-8)	6-7	Resistance to Acid(1~5)	5
Light (Reduced tinting, 1~8)	5	Resistance to Alkali(1~5)	5

^{*}Heat Resistance: the maximum temperature in $^{\circ}$ C at which a change of color (DE \leq 3) occurs after a dwell time of 5 minutes in the barrel of an injection molding machine as per DIN EN 12877-1.

Application & Performance

Recommended for Plastic (PS, SAN, PMMA, PC, PET, PA6, ABS and ABS/PC blends), potential to use in PA66.

Note

Fineland Chem offers innovative pigment technologies designed for long-lastingperformance and consistent quality in industrial use. Product data is based oncurrent knowledge and for reference only. Users should verify suitability; no liability assumed for specific applications.

Date of issue: Sep., 1st 2024

TDS Version: 2.1