

Technical Data Sheet

SPC PB15:1



FINELAND CHEM
泛成化工

General Information

Color Index	Pigment Blue 15:1 (C.I. 74160)
Product Code	DuraPlast®SPC3651
CAS NO.	12239-87-1
EC No.	205-685-1
Chemical Formula	C ₃₂ H ₁₆ CuN ₈ /C ₃₂ H ₁₅ ClCuN ₈

Physical Properties

Pigment Concentration	50%
Appearance	Granular flakes
Density (g/cm ³)	1.55-1.65
PH Value	6-8
Moisture Content (%)	≤1.5
Total impurities(ppm)	≤600

Fastness Properties

Heat Resistance (°C)	230	Alkali Resistance (1-5)	5
Light Resistance (Full Shade, 1-8)	8	Migration Resistance(1-5)	5
Light (Reduced tinting, 1-8)	7	Ethyl Acetate (1-5)	5
Weather Resistance (1-5)	5	Ethanol (1-5)	5
Acid Resistance (1-5)	5	MEK (1-5)	5

Application & Performance

Recommended for Plastic,PO,PVC(PVC & PVC Leather cloth),EVA,ABS,PS,Spun Fiber-PP,potential use in Spun Fiber-Nylon.

Note

Fineland Chem offers innovative pigment technologies designed for long-lasting performance and consistent quality in industrial use. Product data is based on current knowledge and for reference only. Users should verify suitability; no liability is assumed for specific applications.

Date of issue: Sep. 1st, 2024

TDS Version: 2.1

Hangzhou Fancheng Chemical Co.,Ltd.

Add: NO.776, JianSheYi Road, XiaoShan, HangZhou, ZheJiang, China.

Tel: +86-571-83531793

Web: www.finelandchem.com

Fineland Chem Co., Ltd.

Add: Room 09 27/F, Ho King Commercial Centre, 2-16 Fa Yuen Street, Mongkok, K, HK.