Technical Data Sheet



Pigment Red 149

General Information

Color Index	Pigment Red 149 (C.I. 71137)		
Product Code	DuraPlast®3549		
CAS NO.	4948-15-6		
EC No.	225-590-9		
Chemical Formula	$C_{40}H_{26}N_2O_4$		

Physical Properties

Density (g/cm³)	1.29-1.3
Specific Surface Area(m²/g)	59
Oil Absorption (g/100g)	45-50
PH Value	6-7
Bulk Density (lb/gal)	11.7
Total impurities(ppm)	≤600

Fastness Properties

Heat Resistance (°C)	300	Alkali Resistance (1-5)	5
Light Resistance (Full Shade, 1-8)	8	Bleeding Resistance(1-5)	5
Light (Reduced tinting, 1-8)	7	Ethyl Acetate (1-5)	5
Weather Resistance (1-5)	5	Ethanol (1-5)	5
Acid Resistance (1-5)	5	MEK (1-5)	5

Application & Performance

Recommended for Plastic, PO, PVC (PVC & PVC Leather cloth), EVA, ABS, Spun Fiber-PP/PET/Nylon.

Note

*Product specific and application information are based upon our current knowledge. They are non-binding and cannot be taken as guarantee. Users must establish the suitability of individual products. We do not accept any liability relating to the use of our products in particular applications.

Date of issue Sep. 1st, 2024

TDS Version 2.1

Tel: +86-571-83531793 Web: www.finelandchem.com Add Room 09 27/F, Ho King Commercial Centre, 2-16 Fa Yuen Street, Mongkog, KI, HK